
LAUNDRY LOCK OUT SPECIFICATIONS

Little Giant Washers

- Hygiene program reaches 203°F
- 4 high temperature sanitizing programs. Reaches temperature then holds that temperature for a specific time
 - 185°F held for 15 minutes
 - 158°F held for 10 minutes
 - 140° held for 20 minutes
 - 104° held for 30 minutes
- 23 customizable programs. Able to change temperatures and spin speeds
- Highest G-force in industry 526G's
- Stainless steel inner and outer wash drums
- Able to hook up card reader and/or coin box for coin-op
- 21 selectable languages in the display
- Cast iron counter weights for lower vibration during high speed extraction
- Frequency drive motor for unlimited programmability of spin speeds.
- Bearing designed for 25,000 operating hours
- Stainless steel casing
- Able to hook up automatic detergent dispenser pump
- Energy Star rated

Little Giant Dryers

- Unperforated stainless steel drum
- Residual moisture sensors – turn the drying program off when desired residual moisture is obtained – reducing drying time and cost
- Reverse tumbling
- 21 selectable languages in the display
- Stainless steel casing

Washer Extractors

- Stainless steel inner and outer wash drums
- Soft mount design
- Holds up to 199 programs

- Hygiene program reaches 203°F. Can reach the temperature then hold that temperature for a specific time to achieve sanitization.
- Validation packages available for the pharmaceutical and healthcare markets
- Highest G-force in industry ranging from 400 – 542 G's
- Multi-tap transformer for connections to 208-240V
- Freely programmable. Can add programs via chip card reader or manually create them in the software
- 5 selectable languages in the display
- Cast iron counter weights for lower vibration during high speed extraction
- Frequency drive motor for unlimited programmability of spin speeds, and wash agitation speeds.
- Bearing designed for 30,000 operating hours
- 180° door swing
- Diagnostic port for service to connect via laptop for greater serviceability
- Powder coated galvanized side panels
- Stainless steel front panels and lids

Dryers

- Unperforated stainless steel drum
- Residual moisture sensors – turn the drying program off when desired residual moisture is obtained – reducing drying time and cost
- Reverse tumbling
- Holds up to 199 programs
- Freely programmable. Can add programs via chip card reader or manually create them in the software
- 5 selectable languages in the display
- Air recycling system - recycles 60% of the hot air. One vent vents to outside the other vent feeds into the heater
- Validation packages available for the pharmaceutical and healthcare markets
- Reversible door with 180° door swing
- Automatic cool down and anti wrinkle mode
- Diagnostic port for service to connect via laptop for greater serviceability
- Powder coated galvanized side panels
- Stainless steel front panels and lids
- Multi-tap transformer for connections to 208-240V