

Commercial 45 lbs / 20 kg Capacity Washer & Dryer
PW 6201 Washer
PT 8507 Dryer



PW 6201 Washer

- 45 lbs / 20 kg load capacity
- Large commercial load capacity
- Stainless steel front with blue powder-coated sides & top
- Stainless steel H-axis Honeycomb™ drum with right-hinged door
- Automatic load redistribution, eliminating off-balance loads
- Soft mount for low machine vibration and ease of installation
- Superior spin speeds for reduced drying times
- Variable speed motor with soft-start for reduced wear and maintenance

Professional Features for Commercial Use

- Profitronic M control, with preset programs for common washing applications
- Enhanced Application Packages available for adding new, specialized programs
- 180° door opening for easy loading and unloading
- Four detergent compartments in front facia
- Connection to optional dosing pumps for liquid detergents
- Multi-language display feature

PT 8507 Dryer

- 55 lbs / 25kg load capacity
- Large commercial load capacity
- Electric heating
- Residual moisture sensors for optimum throughput and results
- Stainless steel front with blue powder-coated sides & top
- Stainless steel Honeycomb™ drum with reversible left-hinged door
- Durable construction with heavy duty components
- Alternating tumbling action for improved garment dispersion
- Hot air recycling for improved efficiency and throughput
- Unique shield design

Professional Features for Commercial Use

- Profitronic M control, with preset programs for common drying applications
- 180° door opening for easy loading and unloading
- Multi-language display feature



Machine Specifications



PW 6201 Washer

- 64.57"H x 36.38"W x 40.94"D
- Includes UG 6020 base (not shown)
- 1091 lbs / 495 kg
- 3 AC 208/230 V 60 Hz
- 3 x 50 A



Honeycomb™ Drum



Profitronic M Controller



Shield Design



PT 8507 Dryer

- 64.57"H x 47.48"W x 39.45"D
- 525 lbs / 238 kg
- 3 AC 208/230 V 60 Hz
- 3 x 80 A



Honeycomb™ Drum



Profitronic M Controller



Shield Design

Machine	PW 6201 Washer	PT 8507 Dryer
Load Capacity	45 lbs/20 kg	55 lbs/25 kg
Machine Exterior - Front	Stainless Steel	Stainless Steel
Machine Exterior - Lid and Sides	Octoblue powder coat, galvanized	Octoblue powder coat, galvanized
Machine Dimensions	64.57" H (w/ base)	64.57" H
	36.38" W	47.48" W
	40.94" D	39.45" D
Drum Volume	52.8 gallon/200 liter	132 gallon/500 liter
Drum Dimensions	26.7" Ø	43.3" Ø
	21.7" deep	20.8" deep
Door Opening	14.6" Ø	-
Drum Type	Honeycomb™ Stainless Steel	Honeycomb™ Stainless Steel
Spin Speed	1100 RPM	-
G-force	460	-
Control Type	Profitronic M	Profitronic M
Net Weight	1091 lbs/495 kg	525 lbs/238kg
Electrical Connection (Standard)	3 AC 208 / 230 V 60 Hz	3 AC 208 / 230 V 60 Hz
Fuse Rating	3 x 50	3 x 80
Total Rated Load	19.3 kW	28.3 kW
Required Water Flow Pressure	Min - 30 psi	-
	Max - 145 psi	-
Maximum Floor Load	6067 N	-
Water Connection	3/4"	-
Cold Water Line	3	-
Warm Water Line	1	-
Drain Line	3" vented	-
Vent Diameter	-	6"
Evaporation Rate	-	15 fl oz/minute
Electrical Approvals	Commercial & Residential	