

Commercial 30 lbs / 13 kg Capacity Washer & Dryer
PW 6131 Washer
PT 8337 Dryer



PW 6131 Washer

- 30 lbs / 13 kg load capacity
- Includes base to match dryer height (not shown)
- Large commercial load capacity
- Stainless steel front with blue powder-coated sides & top
- Stainless steel H-axis Honeycomb™ drum with right-hinged door
- Automatic load redistribution, eliminating off-balance loads
- Soft mount for low machine vibration and ease of installation
- Superior spin speeds for reduced drying times
- Variable speed motor with soft-start for reduced wear and maintenance

Professional Features for Commercial Use

- Profitronic M control, with preset programs for common washing applications
- Enhanced Application Packages available for adding new, specialized programs
- 180° door opening for easy loading and unloading
- Four detergent compartments in front facia
- Connection to optional dosing pumps for liquid detergents
- Multi-language display feature

PT 8337 Dryer

- 30 lbs / 13 kg load capacity
- Large commercial load capacity
- Electric heating
- Residual moisture sensors for optimum throughput and results
- Stainless steel front with blue powder-coated sides & top
- Stainless steel Honeycomb™ drum with reversible left-hinged door
- Durable construction with heavy duty components
- Alternating tumbling action for improved garment dispersion
- Hot air recycling for improved efficiency and throughput
- Unique shield design

Professional Features for Commercial Use

- Profitronic M control, with preset programs for common drying applications
- 180° door opening for easy loading and unloading
- Multi-language display feature



Machine Specifications



PW 6131 Washer

- 55.12"H x 31.65"W x 39.57"D
- Includes UG 6013 base (not shown)
- 754 lbs / 342 kg
- 3 AC 208/230 V 60 Hz
- 3 x 50 A



Honeycomb™ Drum



Profitronic M Controller



Shield Design



PT 8337 Dryer

- 55.12"H x 35.67"W x 40.12"D
- 364 lbs / 165 kg
- 3 AC 208/230 V 60 Hz
- 3 x 50 A



Honeycomb™ Drum



Profitronic M Controller



Shield Design

| Machine | PW 6131 Washer | PT 8337 Dryer |
|----------------------------------|----------------------------------|----------------------------------|
| Load Capacity | 30 lbs/13 kg | 30 lbs/13 kg |
| Machine Exterior - Front | Stainless Steel | Stainless Steel |
| Machine Exterior - Lid and Sides | Octoblue powder coat, galvanized | Octoblue powder coat, galvanized |
| Machine Dimensions | 55.12" H (w/ base) | 55.12" H |
| | 31.65" W | 35.67" W |
| | 39.57" D | 40.12" D |
| Drum Volume | 34.3 gallon/130 liter | 85.9 gallon/325 liter |
| Drum Dimensions | 23.2" Ø | 33.5" Ø |
| | 18.7" deep | 22.9" deep |
| Door Opening | 14.6" Ø | - |
| Drum Type | Honeycomb™ Stainless Steel | Honeycomb™ Stainless Steel |
| Spin Speed | 1100 RPM | - |
| G-force | 400 | - |
| Control Type | Profitronic M | Profitronic M |
| Net Weight | 754 lbs/342 kg | 364 lbs/165 kg |
| Electrical Connection (Standard) | 3 AC 208 / 230 V 60 Hz | 3 AC 208 / 230 V 60 Hz |
| | | |
| Fuse Rating | 3 x 50 | 3 x 50 |
| | | |
| Total Rated Load | 17 kW | 18.8 kW |
| Required Water Flow Pressure | Min - 30 psi | - |
| | Max - 145 psi | - |
| Maximum Floor Load | 4304 N | - |
| Water Connection | 3/4" | - |
| Cold Water Line | 3 | - |
| Warm Water Line | 1 | - |
| Drain Line | 3" vented | - |
| Vent Diameter | - | 6" |
| Evaporation Rate | - | 10 fl oz/minute |
| Electrical Approvals | Commercial & Residential | |
| | | |
| | | |
| | | |